

Contents

| | <i>Page</i> |
|---|-------------|
| Preface | xix |
| UNICOS system administration publications | xix |
| Related publications | xx |
| Ordering Cray Research publications | xxii |
| Conventions | xxii |
| Reader comments | xxiv |
| | |
| Introduction [1] | 1 |
| The UNICOS system administrator | 1 |
| Create and maintain a log book | 1 |
| Major features of UNICOS | 2 |
| Cray Scalable I/O (SIO) | 2 |
| File systems | 3 |
| Disk devices | 3 |
| File system quotas | 3 |
| User database (UDB) | 3 |
| Resource control | 3 |
| Unified Resource Manager (URM) | 3 |
| Fair-share scheduler | 4 |
| System accounting | 4 |
| TCP/IP | 4 |
| Menu system | 4 |
| Data migration | 4 |
| System activity monitor (SAM) | 5 |
| Network Queuing Environment (NQE) | 5 |
| | |
| SG-2210 10.0 | iii |

| | <i>Page</i> |
|--|-------------|
| How this guide will help you | 5 |
| UNICOS on-line glossary | 8 |
| Cray Scalable I/O Overview [2] | 9 |
| Introduction to Cray scalable I/O | 9 |
| I/O nodes | 10 |
| Single-purpose nodes | 12 |
| Multipurpose node | 14 |
| Solid-state storage device | 16 |
| System workstation for GigaRing environments | 16 |
| Basic System Security [3] | 17 |
| Related basic system security documentation | 17 |
| Monitoring system security | 17 |
| Super-user privileges | 18 |
| Password security for super user | 18 |
| Physical security | 19 |
| setuid programs | 19 |
| root PATH | 20 |
| User security | 21 |
| The umask utility | 21 |
| Default PATH variable | 21 |
| User groups | 22 |
| File-owner fraud | 22 |
| Login attempts | 23 |
| Partition security | 23 |
| Tape device access | 23 |
| Startup and Shutdown [4] | 25 |

| | <i>Page</i> |
|---|-------------|
| Related startup and shutdown documentation | 25 |
| Booting the default configuration | 25 |
| Procedure 1: Booting your system | 26 |
| Multiuser mode | 28 |
| Typical tasks you can perform while in multiuser mode | 29 |
| Dedicated system | 30 |
| Run-level configuration | 30 |
| Changing run level | 30 |
| Strategies for using run levels | 31 |
| Procedure 2: Shutting down UNICOS | 31 |
| File Systems [5] | 35 |
| UNICOS file systems | 35 |
| Related file systems documentation | 35 |
| An overview of file systems | 36 |
| Terminology | 37 |
| UNICOS file system structure | 39 |
| Commands for examining files and file systems | 40 |
| File system planning | 42 |
| The root (/) file system | 43 |
| The /usr file system | 43 |
| The /usr/src file system | 43 |
| The /opt file system | 44 |
| The /tmp file system | 44 |
| The swap device | 44 |
| The dump device | 45 |
| The back-up root (/) and back-up /usr file systems | 45 |
| The /home file system | 45 |

| | <i>Page</i> |
|--|-------------|
| Disk striping | 45 |
| Disk banding | 46 |
| Configuring your devices and their file system allocation | 46 |
| Network disk array configuration | 47 |
| CSL syntax | 47 |
| Identifier | 47 |
| Constants | 48 |
| Operators, separators, and comments | 48 |
| Placement of CSL statements | 48 |
| gigaring section | 49 |
| The gr_route subsection | 50 |
| The gr_union subsection | 50 |
| mainframe section | 51 |
| Number of CPUs | 52 |
| Number of mainframe cluster registers | 52 |
| Size of memory | 52 |
| Example of the mainframe section for a GigaRing based system | 53 |
| unicos section | 53 |
| Example for a GigaRing based system | 56 |
| filesystem section | 56 |
| Physical device definition for GigaRing based systems | 57 |
| Device node definition | 60 |
| Root, swap, and secondary data segment (SDS) devices | 62 |
| Example of the filesystem section containing a RAM file system | 62 |
| Example of the filesystem section for a GigaRing based system | 62 |
| network section | 63 |
| Network parameters | 64 |
| Network devices | 66 |
| Device types | 67 |

| | <i>Page</i> |
|--|-------------|
| Device formats for GigaRing based systems | 67 |
| Network section example for GigaRing based systems | 68 |
| revision section | 68 |
| Checking your disk configuration parameter file | 69 |
| Procedure 3: Verifying your disk configuration file | 69 |
| Procedure 4: Identifying devices defined on your system and their file system allocation | 73 |
| Procedure 5: Modifying your configuration file | 76 |
| File system quotas | 78 |
| File system quota overview | 78 |
| Quota control structure | 78 |
| Commands | 79 |
| Quotas and the user | 80 |
| Quota header file | 80 |
| Soft quotas | 81 |
| Procedure 6: Setting up a quota control file | 81 |
| Current usage information | 84 |
| Warning windows | 84 |
| Sharing quota controls files between multiple file systems | 85 |
| Monitoring quotas | 85 |
| Planning file system change | 86 |
| Configuration objectives | 86 |
| Plan preparation | 86 |
| New disks | 87 |
| Implementation | 87 |
| Apply changes | 88 |
| As you proceed | 88 |
| Helpful hints for implementing plan | 89 |
| Creating file systems | 90 |

| | <i>Page</i> |
|--|-------------|
| Procedure 7: Create the file system | 91 |
| Example 1: round-robin, first-level | 93 |
| Example 2: round-robin, all-directory | 93 |
| Example 3: round-robin, all-files | 93 |
| Example 4: assign file system name and volume name to unmounted file system | 94 |
| Example 5: labelit output | 94 |
| /etc/mnttab and /etc/fstab files | 100 |
| /etc/mnttab | 100 |
| /etc/fstab | 100 |
| Procedure 8: Configuring a file system to be mounted automatically at the initialization of multiuser mode | 101 |
| Procedure 9: Unmounting file systems | 102 |
| Backing Up and Restoring File Systems [6] | 105 |
| Related backup and restore documentation | 105 |
| Tape devices referenced in /dev/tape | 106 |
| Backup and restore utilities | 106 |
| dump and restore utilities | 106 |
| rdump and rrestore utilities | 106 |
| dd utility | 107 |
| tar and cpio utilities | 107 |
| root and usr file systems | 107 |
| Procedure 10: Creating bkroot and bkusr file systems | 107 |
| Procedure 11: Booting bkroot and bkusr into production | 109 |
| Procedure 12: Backing up the SWS | 112 |
| /etc/dump utility | 112 |
| Routine backup (dump) strategy | 113 |
| Restoring file systems | 114 |
| Increasing and decreasing file system space | 115 |

| | <i>Page</i> |
|---|-------------|
| Tape devices | 115 |
| Procedures included in this section | 116 |
| Procedure 13: Backing up (dumping) a file system without <code>tpdaemon</code> | 116 |
| Procedure 14: Restoring a file system without <code>tpdaemon</code> | 118 |
| Procedure 15: Restoring a partial file system by using <code>tpdaemon</code> | 123 |
| Procedure 15.a: Partial file system restore | 124 |
| Maintaining Users [7] | 129 |
| Related user accounts documentation | 129 |
| The user database (UDB) | 130 |
| Adding user records to the UDB | 131 |
| UDB files and commands | 131 |
| Procedure 16: Determining settings for UDB fields | 134 |
| Procedure 17: Adding a group to <code>/etc/group</code> | 138 |
| Procedure 18: Adding an accounting group to <code>/etc/acid</code> | 139 |
| Using the <code>/etc/nu</code> utility | 140 |
| Procedure 19: Changing <code>/etc/nu</code> configuration parameters | 141 |
| Procedure 20: Creating a file system to use with <code>/etc/nu</code> | 143 |
| Procedure 21: Adding a user record to <code>/etc/udb</code> by using <code>/etc/nu</code> | 144 |
| Procedure 22: Modifying user records by using <code>/etc/nu</code> | 149 |
| Procedure 23: Deleting a user record by using <code>/etc/nu</code> | 152 |
| Example 6: <code>/etc/nu</code> session that disables and removes a user's login | 153 |
| Using <code>/etc/udbgen</code> | 155 |
| Procedure 24: Adding users to <code>/etc/udb</code> by using <code>/etc/udbgen</code> | 157 |
| Example 7: Example of using a private copy of UDB files for test purposes: | 163 |
| Procedure 25: Transferring initial files to the login directory when using <code>/etc/udbgen</code> | 163 |
| Procedure 26: Updating user logins in the UDB by using <code>/etc/udbgen</code> | 164 |
| Example 8: Adding a new group ID | 165 |

| | <i>Page</i> |
|--|----------------|
| Example 9: Changing the user's shell | 165 |
| Example 10: Changing the user's login directory | 165 |
| Example 11: Using the udbsee command as a filter to add an account ID (acid) | 166 |
| Example 12: Changing the user's password | 166 |
| Procedure 27: Deleting a user from the UDB by using /etc/udbgen | 166 |
| Maintaining user environment files | 167 |
| Procedure 28: Setting up an /etc/profile file | 168 |
| Procedure 29: Setting up an /etc/cshrc file | 169 |
| Procedure 30: Transferring user accounts to another file system | 170 |
| Communicating with Users [8] | 173 |
| Related user communication documentation | 173 |
| Communicating with users | 173 |
| The wall command | 174 |
| The /etc/motd file | 175 |
| The /etc/issue file | 175 |
| The /usr/news directory | 175 |
| The write utility | 176 |
| The mail utility | 178 |
| Log Files [9] | 179 |
| Related log files documentation | 180 |
| /etc/boot.log file | 180 |
| /etc/rc.log file | 180 |
| /etc/syslog.conf file | 180 |
| System logs | 181 |
| Message sources | 182 |
| Priority levels | 182 |
| syslog daemon startup | 183 |

| | <i>Page</i> |
|--|-------------|
| /usr/adm/sulog | 185 |
| /etc/dump.log | 185 |
| /usr/adm/nu.log | 186 |
| /usr/adm/sa/saDD | 187 |
| /usr/adm/sl/slogfile | 187 |
| /usr/spool/msg/msglog.log | 188 |
| /usr/lib/cron/cronlog | 188 |
| /usr/tmp/nqs.log | 189 |
| /usr/adm/errfile | 190 |
| /usr/spool/dm/* | 191 |
| Cleaning up system logs | 192 |
| Log files recycled during each reboot | 192 |
| Small accumulative log files | 192 |
| Large accumulative log files | 193 |
| Accounting [10] | 195 |
| Cray Research system accounting (CSA) | 195 |
| Concepts and terminology | 197 |
| Files and directories overview | 198 |
| Structures of the acct and tmp directories | 198 |
| Shell scripts and C binaries | 198 |
| Unprocessed data files | 199 |
| Data files being processed | 199 |
| Processed data files | 200 |
| Reports | 201 |
| Daily operation overview | 201 |
| Setting up CSA | 203 |
| The csarun command | 207 |
| Daily invocation | 208 |

| | <i>Page</i> |
|--|-------------|
| Error and status messages | 208 |
| States | 208 |
| Restarting <code>csarun</code> | 210 |
| Verifying and correcting data files | 212 |
| Fixing <code>wtmp</code> errors | 212 |
| Verifying data files | 212 |
| Editing data files | 212 |
| Files and directories | 214 |
| <code>/usr/adm/acct</code> directory | 214 |
| <code>/etc</code> directory | 219 |
| <code>/etc/config</code> directory | 219 |
| CSA data processing | 220 |
| Data recycling | 222 |
| How sessions are terminated | 223 |
| Why recycled sessions should be scrutinized | 224 |
| How to remove recycled data | 224 |
| Adverse effects of removing recycled data | 226 |
| NQS requests and recycled data | 228 |
| Tailoring CSA | 229 |
| System billing units (SBUs) | 230 |
| Daemon accounting | 241 |
| Setting up user exits | 241 |
| Charging for NQS jobs | 242 |
| Tailoring CSA shell scripts and commands | 243 |
| Using <code>at</code> to execute <code>csarun</code> | 243 |
| Allowing nonsuper users to execute CSA | 244 |
| Using an alternate configuration file | 245 |
| Disk usage reporting (<code>diskusg</code>) | 245 |

| | <i>Page</i> |
|--|-------------|
| Per-process accounting data | 246 |
| Base accounting record | 246 |
| End-of-job accounting record | 249 |
| Multitasking accounting record | 249 |
| SDS accounting record | 250 |
| MPP accounting record | 250 |
| Performance accounting record | 251 |
| Multitasking incentives | 251 |
| Memory integrals | 252 |
| Reducing charges | 253 |
| Socket accounting | 254 |
| Device accounting | 254 |
| Categories of devices | 255 |
| Structures and device names | 255 |
| Configuration changes | 256 |
| System header files | 256 |
| Using device accounting (devacct(8)) | 257 |
| Switching / and /usr file systems | 259 |
| Logging information | 259 |
| Boot log | 260 |
| cron log | 260 |
| Dump log | 261 |
| New user log | 261 |
| su log | 261 |
| OLDSu log | 262 |
| System logs | 262 |
| Error log | 264 |

| | <i>Page</i> |
|---|----------------|
| Multilevel security (MLS) log | 264 |
| System activity log | 265 |
| Message log | 265 |
| Accounting logs | 266 |
| NQS log | 267 |
| Adding Your Cray Research System to Your Network [11] | 269 |
| Related network information | 269 |
| Procedure 31: Adding a CRAY J90se system to an existing TCP/IP network | 270 |
| TCP/IP path between J90se and SWS | 275 |
| Procedure 32: Start TCP/IP from mainframe | 276 |
| Changing the SWS host name and IP address | 276 |
| Procedure 33: Changing the SWS host name and IP address | 276 |
| Changing the CRAY J90se host name and IP address | 277 |
| Backing up all changes | 277 |
| Verifying the UNICOS configuration file | 277 |
| Rebooting in multiuser mode | 278 |
| Procedure 34: Rebooting in multiuser mode | 278 |
| Domain name service (DNS) | 278 |
| Procedure 35: Configuring a caching-only server by using the menu system | 279 |
| Procedure 36: Configuring a caching-only server without using the menu system | 282 |
| Common TCP/IP configuration files | 284 |
| Configuring NIS [12] | 287 |
| Related NIS documentation | 287 |
| What is NIS? | 287 |
| Procedure 37: Using the menu system to configure your CRAY J90se system as an NIS slave server | 290 |
| Procedure 38: Configuring your CRAY J90se system as an NIS slave server without using the menu system | 292 |

| | <i>Page</i> |
|--|----------------|
| Procedure 39: Configuring user accounts to use NIS | 294 |
| Configuring NFS [13] | 297 |
| Related NFS documentation | 297 |
| What is NFS? | 297 |
| ID mapping and when it is used | 298 |
| Procedure 40: Configuring a CRAY J90se system as an NFS client | 299 |
| Procedure 41: Configuring a CRAY J90se system as an NFS server | 304 |
| Appendix A Menu System Overview | 309 |
| Accessing and initiating the menu system | 309 |
| Selecting components to maintain by using the menu system | 310 |
| Menu support for full system build | 311 |
| Menu prompts | 311 |
| Menu keys | 312 |
| Menu definition files | 313 |
| Sample process of using a menu | 314 |
| Restoring a configuration | 315 |
| Viewing the /etc/install/install.log log file | 316 |
| Appendix B File Version Numbers | 317 |
| Appendix C Disk Capacities and Transfer Rates | 319 |
| Appendix D Logical Device Cache Process | 321 |
| Setting up ldcache by using /etc/ldcache | 321 |
| Assigning ldcache | 322 |
| Flushing data by using /etc/ldsync | 325 |
| Appendix E Power Up and Down Procedures | 327 |

| | <i>Page</i> |
|---|-------------|
| Procedure 42: Powering up a CRAY J90se system | 327 |
| Procedure 43: Powering down a CRAY J90se system | 327 |
| Appendix F Memory Configuration Parameters | 329 |
| Appendix G IOS and Mainframe Dump | 331 |
| Send dump results to Cray Research | 331 |
| Generating a dump | 331 |
| Index | 333 |
| | |
| Figures | |
| Figure 1. GigaRing channel topology | 9 |
| Figure 2. ddstat output field definitions | 75 |
| Figure 3. /usr/adm/acct and tmp directory structures | 198 |
| Figure 4. CSA program data flow | 220 |
| | |
| Tables | |
| Table 1. Cray scalable I/O product names and descriptions | 11 |
| Table 2. Cray scalable I/O support equipment | 12 |
| Table 3. Peripherals supported by single-purpose nodes | 13 |
| Table 4. Peripherals supported by MPN | 15 |
| Table 5. Online tape parameters | 54 |
| Table 6. Table size parameters | 54 |
| Table 7. Maximum limits parameters | 54 |
| Table 8. Disk parameters (common) | 55 |
| Table 9. Disk parameters (GigaRing based systems only) | 55 |
| Table 10. ION unit bit and range numbers | 56 |
| Table 11. Disk information (GigaRing based systems only) | 58 |
| Table 12. Network parameter values (Common) | 64 |

| | <i>Page</i> |
|--|-------------|
| Table 13. Network parameter values (GigaRing-based systems) | 66 |
| Table 14. Network device types (common) | 67 |
| Table 15. Network device types (GigaRing based systems only) | 67 |
| Table 16. Possible effects of removing recycled data | 228 |
| Table 17. TCP/IP configuration files | 285 |
| Table 18. NBANKS values for CRAY J916se 2X2 backplane | 329 |
| Table 19. NBANKS values for CRAY J916se 4X4 backplane | 329 |
| Table 20. NBANKS values for CRAY J932se 8X8 backplane | 330 |

