

CONTENTS

accept	Accepts a connection on a socket	29
access	Determines accessibility of a file	33
acct	Enables or disables process accounting	37
acctctl	Checks status of, enables, and disables process, daemon, and record accounting	39
acctid	Changes account ID of a process	42
adjtime	Corrects the time to allow synchronization of the system clock	44
alarm	Sets a process alarm clock	46
bind	Binds a name to a socket	49
brk	Changes data segment space allocation	53
bsdsignal (see signal)	Changes action associated with a signal	470
bsd_sigpause (see sigsuspend)	Releases blocked signals and waits for interrupt	483
chacid	Changes disk file account ID	56
chdir	Changes working directory	58
chdiri	Changes a directory by using the inode number	61
chkpnt	Checkpoints a process, multitask group, or job	63
chmem	Retrieves or modifies system physical memory availability	69
chmod	Changes the mode of a file	71
chown	Changes owner and group of a file	75
chroot	Changes the root directory	79
close	Closes a file descriptor	81
cmpext	Compares the supplied character sequence with the privilege text of the calling process	82
connect	Initiates a connection on a socket	84
cpselect	Selects which processors may run the process	88
creat	Creates a new file or rewrites an existing one	90
cutimes	Updates user execution time	94
dacct	Enables or disables process and daemon accounting	97
devacct	Controls device accounting	99
dmmode	Sets and gets data migration retrieval mode	102
dmofrq	Processes offline file requests	103
dup	Duplicates an open file descriptor	107
exctl	Exchanges control	109
exec	Executes a file	111
execl (see exec)	Executes a file	111
execle (see exec)	Executes a file	111
execlp (see exec)	Executes a file	111
execv (see exec)	Executes a file	111
execve (see exec)	Executes a file	111
execvp (see exec)	Executes a file	111
_exit (see exit)	Terminates process	118
exit	Terminates process	118
fchmod (see chmod)	Changes the mode of a file	71
fchown (see chown)	Changes owner and group of a file	75
fcntl	Controls open files	121
fgetpal	Gets the privilege assignment list (PAL) and privilege sets of a file	130
fjoin (see join)	Joins files	221
fork	Creates a new process	131

fpathconf (see pathconf)	Determines value of file or directory limit	299
fsecstat (see secstat)	Gets file security attributes	371
fsetpal	Sets the privilege assignment list (PAL) and privilege sets of a file	136
fstat (see stat)	Gets file status	503
fstatfs (see statfs)	Gets file system information	509
fstatvfs (see statvfs)	Gets file system information	514
fsync	Synchronizes the in-core state of a file with that on disk	138
getash	Gets an array session handle	140
getdents	Reads and formats directory entries as file system independent	141
getdevn	Gets device number or driver entry	143
getegid (see getuid)	Gets real user, effective user, real group, or effective group IDs	197
geteuid (see getuid)	Gets real user, effective user, real group, or effective group IDs	197
getfacl	Gets access control list entries for file	144
getgid (see getuid)	Gets real user, effective user, real group, or effective group IDs	197
getgroups	Gets or sets group list	148
gethostid	Gets or sets unique identifier of local host	151
gethostname	Gets or sets name of local host	153
getinfo	Gets specified user, job, or process signal information	155
getjtab	Gets the job table entry associated with a process	158
getlim	Obtains current resource limit information	160
_getlwpid (see getpid)	Gets process, process group, or parent process IDs	176
_getlwpid (see getpid)	Gets process, process group, or parent process IDs	176
getmount	Returns information about the kernel mount table	163
getpal	Gets the privilege assignment list (PAL) and privilege sets of a file	167
getpeername	Gets name of connected peer	169
getpermit	Gets or sets user permissions	172
getppgrp (see getpid)	Gets process, process group, or parent process IDs	176
getpid	Gets process, process group, or parent process IDs	176
getportbm (see setportbm)	Sets or gets the kernel memory port bit map	420
getppid (see getpid)	Gets process, process group, or parent process IDs	176
getppriv	Gets the privilege state of the calling process	179
getsectab	Gets security names and associated values	180
getsockname	Gets socket name	182
getsockopt	Gets or sets options on sockets	184
getsysv	Gets security attributes	189
gettimeofday	Gets or sets date and time	194
getuid	Gets real user, effective user, real group, or effective group IDs	197
getusrv	Gets security validation attributes of the process	199
_globalexit (see exit)	Terminates process	118
globalexit (see exit)	Terminates process	118
guestctl	Controls and reports the status of major guest system functions	202
ialloc	Allocates storage for a file	211
intro	Introduces system calls and error numbers	1
ioctl	Controls device	214
jacct	Enables or disables job accounting	219
join	Joins files	221
kill	Sends a signal to a process or a group of processes	223
killm (see kill)	Sends a signal to a process or a group of processes	223
lchown (see chown)	Changes owner and group of a file	75
limit	Sets resource limits	227
limits	Returns or sets limits structure for fair-share scheduler	232

link	Creates a link to a file	235
listen	Listens for connections on a socket	239
listio	Initiates a list of I/O requests	243
_localexit (see exit)	Terminates process	118
localexit (see exit)	Terminates process	118
lsecstat (see secstat)	Gets file security attributes	371
lseek	Moves read/write file pointer	249
lsetattr	Sets metadata for a file	252
lstat (see stat)	Gets file status	503
_lwp_alarm (see alarm)	Sets a process alarm clock	46
_lwp_exit (see exit)	Terminates process	118
_lwp_kill (see kill)	Sends a signal to a process or a group of processes	223
_lwp_killm (see kill)	Sends a signal to a process or a group of processes	223
mkdir	Makes a directory	254
mkfifo (see mknod)	Makes a directory or a special or regular file	257
mknod	Makes a directory or a special or regular file	257
mount	Mounts a file system	262
msgctl	Provides message control operations	265
msgget	Accesses the message queue	269
msgrcv	Reads a message from a message queue	271
msgsnd	Sends a message to a message queue	274
mtimes	Provides multitasking execution overlap profile	277
newarraysess	Starts a new array session	279
_newexit (see exit)	Terminates process	118
newexit (see exit)	Terminates process	118
newgetpid (see getpid)	Gets process, process group, or parent process IDs	176
newgetppid (see getpid)	Gets process, process group, or parent process IDs	176
nice	Changes priority of processes	281
nicem (see nice)	Changes priority of processes	281
nsecctl	Accesses or manipulates network security information	284
open	Opens a file for reading or writing	287
openi	Opens a file by using the inode number	297
pathconf	Determines value of file or directory limit	299
pause	Suspends process until signal	305
pipe	Creates an interprocess channel	307
plock	Locks process in memory	310
policy	Returns or sets information on the CPU allocation policy	312
profil	Generates an execution time profile	314
ptrace	Traces processes	316
ptyrecon	Manages pty reconnection	320
quotactl	Manipulates file system quotas	322
read	Reads from file	329
reada	Performs asynchronous read from a file	333
readlink	Reads value of a symbolic link	339
recall	Waits for I/O completions	342
recalla	Waits for I/O completion(s)	344
recalls (see recall)	Waits for I/O completions	342
recv	Receives a message from a socket	347
recvfrom (see recv)	Receives a message from a socket	347
recvmsg (see recv)	Receives a message from a socket	347
rename	Changes the name of a file	352

resch	Reschedules a process	356
restart	Restarts a process, multitask group, or job	357
resume (see suspend)	Controls execution of processes	518
rmdir	Removes a directory	363
rmfacl	Removes an access control list from a file	366
sbreak (see brk)	Changes data segment space allocation	53
sbrk (see brk)	Changes data segment space allocation	53
schedv	Sets memory scheduling parameters	368
secstat	Gets file security attributes	371
select	Examines synchronous I/O multiplexing	374
semctl	Provides semaphore control operations	378
semget	Provides access to semaphore identifiers	383
semop	Provides general semaphore operations	386
send	Sends a message from a socket	390
sendmsg (see send)	Sends a message from a socket	390
sendto (see send)	Sends a message from a socket	390
setash	Sets an array session handle	393
setdevs	Sets file security label and security flag attributes	395
setegid (see setregid)	Sets real or effective group ID	423
seteuid (see setreuid)	Sets real or effective user ID	426
setfacl	Sets access control list for file	398
setfcmp	Sets file compartments	402
setfflg	Sets file security flags	405
setflvl	Sets security level of a file	407
setgid (see setuid)	Sets user or group IDs	438
setgroups (see getgroups)	Gets or sets group list	148
sethostid (see gethostid)	Gets or sets unique identifier of local host	151
sethostname (see gethostname)	Gets or sets name of local host	153
setjob	Sets job ID	409
setlim	Sets user-controllable resource limits	411
setpal	Sets the privilege assignment list (PAL) and privilege sets of a file	414
setpermit (see getpermit)	Gets or sets user permissions	172
setpgid	Sets process-group-ID for job control	416
setpgrp	Sets process-group ID	418
setportbm	Sets or gets the kernel memory port bit map	420
setppriv	Sets the privilege state of the calling process	422
setregid	Sets real or effective group ID	423
setreuid	Sets real or effective user ID	426
setrgid (see setregid)	Sets real or effective group ID	423
setruid (see setreuid)	Sets real or effective user ID	426
setsid	Creates session and sets process group ID	430
setsockopt (see getsockopt)	Gets or sets options on sockets	184
setsysv	Sets minimum and maximum level range, authorized compartments, and security auditing options	431
settimeofday (see gettimeofday)	Gets or sets date and time	194
setucat	Sets active categories of a process	434
setucmp	Sets active compartments of the process	436
setuid	Sets user or group IDs	438
setulvl	Sets the active security level of the process	442
setusrv	Sets security validation attributes of the process	444
shmat	Attaches shared memory segment	447

shmctl	Provides shared memory control operations	450
shmdt	Detaches shared memory segment	455
shmget	Accesses shared memory identifier	457
shutdown	Shuts down part of a full-duplex connection	460
sigaction	Examines or changes action associated with a signal	462
sigblock (see sigprocmask)	Examines and changes blocked signals	479
sigctl	Provides generalized signal control	466
sighold (see sigprocmask)	Examines and changes blocked signals	479
sigignore (see signal)	Changes action associated with a signal	470
signal	Changes action associated with a signal	470
sigpause (see sigsuspend)	Releases blocked signals and waits for interrupt	483
sigpending	Stores pending signals	477
sigprocmask	Examines and changes blocked signals	479
sigrelse (see sigprocmask)	Examines and changes blocked signals	479
sigset (see signal)	Changes action associated with a signal	470
sigsetmask (see sigprocmask)	Examines and changes blocked signals	479
sigsuspend	Releases blocked signals and waits for interrupt	483
sigvec (see sigaction)	Examines or changes action associated with a signal	462
slgentry	Makes security log entry	486
socket	Creates an endpoint for communication	488
socketpair	Creates a pair of connected sockets	495
ssbreak	Changes size of secondary data segment	497
ssread	Reads or writes to secondary data segment	500
sswrite (see ssread)	Reads or writes to secondary data segment	500
stat	Gets file status	503
statfs	Gets file system information	509
statvfs	Gets file system information	514
stime	Sets time	517
suspend	Controls execution of processes	518
symlink	Makes a symbolic link to a file	522
sync	Flushes system buffers out of main memory	526
sysconf	Retrieves system implementation information	528
sysfs	Gets file system type information	533
syssgi	Provides a system interface to Silicon Graphics workstations	536
tabinfo	Returns information on and reads a system table	538
tabread (see tabinfo)	Returns information on and reads a system table	538
target	Retrieves or modifies machine characteristics	541
tcgetpgrp	Gets or sets terminal process group ID of the foreground process group	543
tcsetpgrp (see tcgetpgrp)	Gets or sets terminal process group ID of the foreground process group	543
_tfork	Creates a multitasking process	545
thread	Registers this process as a thread	546
_threadexit (see exit)	Terminates process	118
time	Gets time	548
times	Gets process and child process times	550
trunc	Truncates a file	552
ulimit	Gets and sets user limits	555
umask	Sets and gets file creation mask	558
umount	Unmounts a file system	560
uname	Gets name of current operating system	562
unlink	Removes directory entry	564
unlink2 (see unlink)	Removes directory entry	564

upanic	Stops the system from a user process	569
ustat	Gets file system statistics	571
utime	Sets file access and modification times	573
vfork	Creates a new process in a memory efficient way	577
wait	Waits for a child process to stop or terminate	580
waitjob	Gets information about a terminated child job	586
waitpid (see wait)	Waits for a child process to stop or terminate	580
wracct	Writes an accounting record to the kernel accounting file or to a daemon accounting file	588
write	Writes on a file	590
writea	Performs asynchronous write on a file	596