

Reserved Keywords in CSL [A]

The following keywords have special meaning in the configuration specification language (CSL):

| | |
|---------|---------|
| 12MB | DD39 |
| 12MB_LP | DD4 |
| 6MB | DD40 |
| A130 | DD41 |
| A400 | DD42 |
| ALL | DD49 |
| C90M | DD50 |
| C90 | DD501 |
| CNT | DD5I |
| D90 | DD5S |
| DA301 | DD60 |
| DA302 | DD61 |
| DA60 | DD62 |
| DA62 | DD65 |
| DD10 | DD6S |
| DD11 | DD7S |
| DD19 | DDAS |
| DD1MEM | DDAS2 |
| DD29 | DDES DI |
| DD3 | DDIMEM |
| DD301 | DDL DAS |
| DD302 | DD_U |
| DD314 | DIAG |
| DD318 | DX4130 |

| | |
|----------|------------|
| DX8130 | I_field |
| EN643 | LCP |
| FEI_3FY | LDCHCORE |
| FEI_3 | LDDMAX |
| FEI_4 | LLC |
| FEI_CN | MDDSLMAX |
| FEI_DS | MP |
| FEI_UC | Mword |
| FEI_VA | Mwords |
| FEI_VB | N130 |
| FEI_VM | N400 |
| FY | NBUF |
| GATEWAYS | NGRT |
| GUESTMAX | NLDCH |
| Gword | NPARTITION |
| Gwords | NPBUF |
| HD16 | NPLCHCTL |
| HD32 | NPOOL |
| HD64 | NSC_MP |
| HDDMAX | NTRANSACT |
| HDDSLMAX | NTTYDEV |
| I/O | NYPEDEV |
| IMP_3 | OLNET |
| IMP_4 | PBUFSIZE |
| IMP_5 | PB |
| IMP_6 | PDDMAX |
| IMP_7 | PDDSLMAX |
| | PLCHCORE |

| | |
|------------------|---------------------|
| PS_32 | alternate |
| P_8 | atmarp_entries |
| RAM | atmarp_recv |
| RAW | atmarp_send |
| RD-1 | atmdev |
| RDDSLMAX | atmmaxdevs |
| REGT | bank |
| SBUFSIZE | bias |
| SDDSLMAX | block |
| SMT | blocks |
| SSD | boot |
| SSDDSLMAX | bootable |
| SSD_E | both |
| SSD_F | c100d100 |
| SSDTMAX | c100d200 |
| SSDTSLMAX | c200d200 |
| T3D | channel |
| T90_config | cluster |
| TAPE_MAX_CONF_UP | clusters |
| TAPE_MAX_DEV | cnfs_static_clients |
| TAPE_MAX_PER_DEV | cnfs_temp_clients |
| TCP | config |
| ULP_id | cpu |
| VAXBI | cpus |
| VME | cylinder |
| XDDMAX | cylinders |
| XDDSLMAX | device |
| access | disk |

| | |
|-------------|-----------------|
| dmpdev | halfs |
| driver | halves |
| dumpinfo | hdd |
| eiop | hidev |
| emulate | hidirmode |
| endev | hifilemode |
| enmaxdevs | himaxdevs |
| enmaxpaths | himaxpaths |
| fddev | hippi_disk |
| fddirmode | hisp |
| fdfilemode | ifield |
| fdmaxdevs | input |
| fdmaxpaths | iopath |
| fiber_vhisp | iounit |
| filesystem | ios_e |
| flags | io_connect |
| function | is |
| gateway | ldd |
| gatm | length |
| gether | logical |
| gfddi | logical_machine |
| ghippi | lower |
| gigaring | lowspeed |
| group | mainframe |
| gr_route | maintenance |
| gr_union | maxrd |
| half | maxinputs |

| | |
|--------------------|------------|
| maxoutputs | npfilemode |
| maxusers | npito |
| maxwrt | npmaxdevs |
| mdd | npmaxpaths |
| memory | npmaxppd |
| minor | npoto |
| miop | nprthresh |
| mode | nprto |
| mpp | npwthresh |
| muxiop | output |
| network | owner |
| nfs_duptimeout | ows |
| nfs_maxdata | padcnt |
| nfs_maxdupreqs | path |
| nfs_num_rnodes | pdd |
| nfs_printinter | phase_III |
| nfs_static_clients | physical |
| nfs_temp_clients | profile |
| nfs_wcredmax | pseudo |
| nfs3_async_max | qdd |
| nfs3_async_time | range |
| no-direction | read |
| no | register |
| node | revision |
| np_spec | ring |
| npdev | rft |
| npdirmode | rootdev |

| | |
|---------------|---------|
| route | timeout |
| sdd | to |
| ssdt | track |
| sdsdev | tracks |
| section | treq |
| sector | type |
| sectors | unicos |
| select | unit |
| serial | upper |
| spare | vhispl |
| spares | with |
| start | word |
| stream | words |
| subsection | write |
| swapdev | xdd |
| system | |
| tcp_nmbpspace | |