

A

- Access request logging, 20
- ACNICE, 11
- Address resolution protocol (ARP), 74
- Adjust-on-exit value , 16
- ARP
 - (See Address resolution protocol), 74
- Async write cache, 23
- Asynchronous I/O headers, 8
- Asynchronous I/O headers reserved for the system , 10
- Asynchronous I/O structures allowed per process, 8
- Asynchronous transfer mode, 76
- Asynchronous transfer mode (ATM) address resolution protocol (ARP), 74
- asynchronously written data , 23
- at.allow file, 92
- at.deny file, 92
- ATM
 - (See Asynchronous transfer mode), 74
- atmarp_entries parameter, 74
- atmarp_rcv parameter, 74
- atmarp_send parameter, 75
- atmmxdevs parameter, 76
- Audit criteria logging , 21
- Automatic mixed buffer, 11

B

- Bit matrix multiply functional unit, 31
- Bits per memory chip, 4
- Boot process in CSL, 35
- boot statement, 43
- brc shell script, 93
- Buffer cache factor, 8
- Buffer headers, 50

- Buffer size for NFS data, 75
- Buffers, 76
- Bus Based Gateway, 31

C

- C default, 29
- Cache, 75
- Cache blocks based on memory size, 9
- Cache size of duplicate requests (NFS_MAXDUPREQS), 24
- Callout table entries, 9
- CDLIMIT, 8
- Channel assignments, 48
- Channel declarations
 - GigaRing based systems, 46
 - IOS-E based systems, 48
- Channel information, 41
- channel statement
 - GigaRing based systems, 46
 - IOS-E based systems, 48
- chdir request logging, 21
- Checkpoint and restart buffers, 9
- Chip size, 4
- CHIPSZ , 4
- Client handles in CNFS, 24
- Client handles in CNFS, 24
- Client handles in NFS, 24
- clist, 9
- Clock period, 6
- cluster, 49
- cluster statement, 42
- Clusters , 41
 - (See Configuration specification language (CSL) parameter file), 42
- CNFS_STATIC_CLIENTS, 24
- cnfs_static_clients, 25

- cnfs_static_clients parameter, 75
- CNFS_TEMP_CLIENTS, 24
- cnfs_temp_clients, 25
- cnfs_temp_clients parameter, 75
- Comments in CSL, 35
- COMPART_ACTIVE_DEFAULT, 17
- COMPART_VALID_DEFAULT, 17
- config.h configuration file, 7
- config.h configuration file, 1
 - CNFS_STATIC_CLIENTS, 24
 - CNFS_TEMP_CLIENTS, 24
 - MSGMNI, 15
 - MSGSSZ, 16
 - NFS kernel parameters, 23
 - NFS3_ASYNC_TIME, 23
 - NFS_PRINTINTER, 24
 - NFS_STATIC_CLIENTS, 24
 - NPBUF, 10
 - NPLCHCTL, 10
 - security log (SLG_STATE), 22
 - SLG_STATE, 22
 - static client handles in CNFS
 - (CNFS_STATIC_CLIENTS), 24
 - static client handles in NFS
 - (NFS_STATIC_CLIENTS), 24
 - temporary client handles
 - (CNFS_TEMP_CLIENTS), 24
 - temporary client handles
 - (NFS_TEMP_CLIENTS), 24
 - U_MAXPACK, 11
- config.mh configuration file for UNICOS kernel subsystems, 27
- config.mh configuration file for UNICOS kernel subsystems, 1
 - CONFIG_CRAYLIBS, 32
- CONFIG_BBG, 31
- CONFIG_BMM, 31
- CONFIG_CPP, 29
- CONFIG_CPSAVE, 29
- CONFIG_CRAYLIBS, 32
- CONFIG_CRL, 31
- CONFIG_CVT, 31
- CONFIG_DFS, 31
- CONFIG_DIAGDIR, 27
- CONFIG_DM parameter, 31
- CONFIG_ELS, 31
- CONFIG_FQUOTAS, 31
- CONFIG_GCC, 29
- CONFIG_GEN_SEGDIR, 29
- CONFIG_GENBIN, 30
- CONFIG_GENCMDS, 30
- CONFIG_GENPROD_RULES, 30
- CONFIG_HPI3, 31
- CONFIG_HSX, 31
- CONFIG_ID, 27
 - GigaRing based systems, 28
 - IOS-E based systems, 29
- CONFIG_IOS-F
 - GigaRing based systems, 28
 - IOS-E based systems, 29
- CONFIG_IOSA_SN, 29
- CONFIG_IOSB_SN, 29
- CONFIG_IPI3, 31
- CONFIG_KERBEROS, 31
- CONFIG_LD_STD_DIR parameter, 32
- CONFIG_MIXED, 31
- CONFIG_MIXEDTARGET, 31
- CONFIG_MK
 - GigaRing based systems, 28
 - IOS-E based systems, 29
- CONFIG_MPP, 31
- CONFIG_MPP_CPP, 30
- CONFIG_NETMON parameter, 31
- CONFIG_NETTOLS, 31
- CONFIG_NFS parameter, 32
- CONFIG_NFS3, 32
- CONFIG_NFSKRB, 32
- CONFIG_NIOS, 29
- CONFIG_NODE, 28
- CONFIG_OWS, 32
- CONFIG_PACKAGE, 30
- CONFIG_PATH, 30
- CONFIG_RLS_MAJOR, 30
- CONFIG_RLS_MINOR, 30
- CONFIG_RLS_REVISION, 30

-
- CONFIG_RPC, 32
 - CONFIG_SN, 28
 - CONFIG_SUPPORT_DIR, 30
 - CONFIG_SYS, 28
 - CONFIG_TAPE, 32
 - CONFIG_TARGET, 28
 - CONFIG_TCP, 32
 - CONFIG_TMPDIR, 28
 - CONFIG_TRUSTED, 32
 - CONFIG_VERSION, 28
 - CONFIG_X11, 32
 - CONFIG_XLIBS, 30
 - CONFIG_XLIBTARGET, 30
 - Configuration
 - shell scripts, 100, 102
 - Configuration logging, 20
 - Configuration specification language
 - boot-time equivalents for NFS kernel parameters, 25
 - Configuration specification language (CSL)
 - parameter file, 1, 33, 51, 74, 75
 - , 81
 - asynchronous transfer mode (ATM) address resolution protocol (ARP), 74
 - ATM devices, 76
 - atmarp_entries parameter, 74
 - atmarp_recv parameter, 74
 - atmarp_send parameter, 74
 - atmmaxdevs parameter, 76
 - boot process and, 35
 - buffer headers, 50
 - buffer size, 75
 - cnfs_static_clients parameter, 75
 - cnfs_temp_clients parameter, 75
 - Cray NFS clients, 75
 - customized network device prototypes for
 - IOS-E based systems , 78
 - device formats
 - GigaRing based systems, 82
 - IOS-E based systems, 83
 - device type statement , 81
 - disk, 57
 - disk parameters
 - common, 51
 - GigaRing based systems, 51
 - IOS-E based systems, 52
 - dumpinfo section, 37
 - duplicate request cache, 75
 - error message syntax, 36
 - Ethernet devices, 77
 - fddi value statement , 81
 - fdmaxdevs parameter, 76
 - fiber distributed data interface (FDDI)
 - (FCA-1) channel adapter, 76
 - gatm device, 82
 - gether device, 82
 - gfddi device, 82
 - ghippi device, 82
 - GigaRing device types, 82
 - gigaring section, 39
 - gr_route subsection, 40
 - gr_union subsection, 40
 - guest resource table entries, 50
 - guest systems, 50
 - GUESTMAX parameter, 50
 - HDDMAX parameter, 52
 - HDDSLMAX parameter, 52
 - hi device, 82
 - hidirmode parameter, 75
 - hifilemode parameter, 75
 - High Performance Parallel Interface, 76
 - himaxdevs parameter, 76
 - himaxpaths parameter, 76
 - HIPPI directory mode, 75
 - HIPPI disk device (HDD) slices, 52
 - HIPPI disk devices (HDDs), 52
 - hippi_disk device type , 57
 - interface configuration templates , 80
 - ios_ section
 - clusters, 42
 - IOP declarations, 42
 - ios_e section, 41
 - HISP declarations, 43
 - IOP boot declarations, 43
 - IPI-2 disk type, 57

- ldcache blocks, 50
- ldcache headers, 50
- LDCHCORE parameter, 50
- LDDMAX parameter, 51
- logical disk devices (LDDs), 51
- logical path statement , 81
- low-speed channel communication devices, 76
- mainframe configuration
 - menu, 44
- mainframe section, 44
 - channel declarations (GigaRing based systems), 46
 - channel declarations (IOS-E based systems), 48
 - common parameters, 45
 - CPUs, 45
 - mainframe cluster registers, 45
 - memory size, 46
- maximum limits parameters, 50
- maxinputs parameter, 76
- maxoutputs parameter, 76
- maxusers parameter, 76
- MDDSLMAX parameter, 51
- mirrored disk device (MDD) slices, 51
- NBUF parameter, 50
- network device types
 - GigaRing based, 82
 - IOS-E based, 82
- network devices, 81
- network parameters
 - common, 74
 - GigaRing based, 76
 - IOS-E based, 76
- network section, 73
 - menu, 73
- NFS requests, 75
- nfs3_async_max parameter, 75
- nfs3_async_time parameter, 75
- nfs_duptimeout parameter, 75
- nfs_maxdata parameter, 75
- nfs_maxdupreqs parameter, 75
- nfs_num_rnodes parameter, 75
- nfs_printinter parameter, 75
- nfs_static_clients parameter, 75
- nfs_temp_clients parameter, 75
- NGRT parameter, 50
- NLDCH parameter, 50
- np_spec statement , 81
- NPBUF parameter, 50
- npdev device, 82
- npfilemode parameter, 76
- npmaxdevs parameter, 76
- npmaxpaths parameter, 76
- npmaxppd parameter, 77
- npoto parameter, 77
- nprthresh parameter, 77
- nprto parameter, 77
- npwthresh parameter, 77
- output time-out, 77
- parameter file sections, 36
 - common, 44, 49, 54, 73
 - GigaRing based systems, 39
 - IOS-E based systems, 37, 41
- PDDMAX parameter, 51
- PDDSLMAX parameter, 51
- physical devices, 52
- physical disk devices (PDDs), 51
- physical I/O buffers, 50
- physical slices, 52
- RAM device type , 57
- RAM disk device (RDD) slices, 51
- RDDSLMAX parameter, 51
- revision section, 89
- rnode table for NFS, 75
- SDDSLMAX parameter, 51
- semicolon in, 35
- Socket space , 74
- SSD device type , 57
- SSD-T90 device type, 57
- SSD-T90 devices, 51
- SSD-T90 slice allocation, 51
- SSDTMAX parameter, 51
- SSDTSLMAX parameter, 51
- statement terminator, 35
- striped disk device (SDD) slices, 51

- syntax
 - comments, 35
 - constants, 34
 - identifier, 33
 - operators, 35
 - separators, 35
 - table size parameters, 50
 - TAPE_MAX_CONF_UP parameter, 50
 - TAPE_MAX_DEV parameter, 50
 - TAPE_MAX_PER_DEV parameter, 50
 - TCP/IP managed memory buffers, 75
 - tcp_numbspace parameter, 75
 - termination of statements, 35
 - token classes, 33
 - unicos section, 49
 - menu, 49
 - usage, 35
 - verification of configurations, 35
 - XDDMAX parameter, 52
 - XDDSLMAX parameter, 52
 - xdisk, 57
 - /CONFIGURATION, 35
 - Console for MLS administration
 - (SYSTEM_ADMIN_CONSOLE), 22
 - CONSOLE_MSG, 17
 - Constants in CSL, 34
 - Contraction value, 13
 - coredd shell script, 93
 - coremap initial dynamic kernel memory units, 13
 - CPP, 30
 - CPP variable, 29
 - CPUs, 6, 45
 - Cray Data Migration Facility (DMF), 31
 - Cray floating-point and IEEE), 31
 - CRAY J90 and CRAY J90se support, 31
 - Cray NFS clients, 75
 - CRAY T3D system, 31
 - Cray Visualization Toolkit, 31
 - cray-t3e assembler, 29
 - Cray/REELlibrarian, 31
 - Cray/REELlibrarian activity logging, 21
 - CRL
 - (See Cray/REELlibrarian), 31
 - cron.allow file, 93
 - cron.deny file, 93
 - Cross-targeted libraries, 30
 - cshrc file, 93
 - CSL
 - (See Configuration specification language (CSL) parameter file), 1
 - CSL reserved keywords, 105
 - Customized network device prototypes for IOS-E based systems, 78
 - CVT
 - (See Cray Visualization Toolkit), 31
 - Cycles per second, 6
- D**
- daemons file, 94
 - Data Migration Facility
 - (See Cray Data Migration Facility), 31
 - data read or written by way of NFS, 23
 - Data written asynchronously, 23
 - DCE
 - (See Distributed Computing Environment), 31
 - Declarations in CSL
 - HISP, 43
 - IOP, 42
 - DECLASSIFY_DISK, 17
 - DECLASSIFY_PATTERN, 17
 - DELAY_MULT, 18
 - Destination routing, 40
 - /dev/comm, 77
 - /dev/fddi*, 77
 - DEV_ENFORCE_ON, 18
 - Device labeling, 18
 - device type statement, 79, 81
 - DFS
 - (See Distributed Computing Environment), 31
 - Directory name look-up cache (DNLC)
 - number of entries, 9

- path name , 9
- Disable a parameter, 7
- DISABLE_ACCT, 18
- DISABLE_TIME, 18
- Discretionary access control (DAC) logging, 21
- Discretionary access violations, 20
- disk, 56, 57
- Distributed Computing Environment (DCE)
 - distributed file system (DFS)
 - (CONFIG_DFS), 31
- DMA driver, 40
- DMF
 - (See Cray Data Migration Facility), 31
- DMODE , 8
- Dump requirements, 37
- dumpinfo section, 37
- Duplicate request cache, 75
- Duplicate request cache size , 24
- Duplicate time-out, 23
- Dynamic kernel memory parameters, 12

E

- econfig command and configuration
 - verification, 36
- eiop statement, 42
- Enable a parameter, 7
- enmaxdevs, 77
- Environment variables
 - definitions in rcoptions file, 102
- Error exit maximum, 15
- Error message syntax for CSL, 36
- Error messages and CSL, 36
- /etc/config/param, 33
- Ethernet devices, 77
- Examples
 - filesystem section, 68
 - CRAY SSD-T90, 71
 - GigaRing based, 69, 71
 - SSD for IOS-E based, 73
 - third-party I/O, 70
 - ios_e section, 43

- mainframe section
 - GigaRing based systems, 49
 - IOS-E based systems, 49
- unicos
 - CRAY SSD-T90 (additional parameters), 53
 - GigaRing based systems, 53
 - IOS-E based systems, 53
- exec operations, 9
- exec operations with maximum arguments , 11
- executables (CONFIG_GENCMDS), 30
- Expansion units, 12
- EXTDCORE, 8
- Extended core file naming, 8

F

- Failed login attempt logging, 22
- Failed logins, 18
- Fair share scheduler, number of users, 10
- FCN bit and range numbers, 52
- fddev device format, 84
- FDDI channel, 77
- fddi value statement, 81
- fddirmode, 77
- fdfilemode, 77
- fdmaxdevs parameter, 76
- fdmaxpaths, 77
- Fiber distributed data interface (FDDI) (FCA-1)
 - channel adapter, 76
- File mode permission, 77
- File quotas, 31
- File retrieval mode, 8
- File size in blocks, 8
- File system log records, 11
- File systems open concurrently , 9
- File systems that can be mounted, 10
- file transfer logging, 20
- File-lock regions (NFLOCKS) , 9
- Files that can be open at one time system-wide
 - (NFILE) , 9
- filesystem section, 54

Flush buffered data to target I/O devices, 8
 FLUSHONPANIC, 8
 FORCED_SOCKET, 18
 FSETID_RESTRICT parameter, 18
 FSLG_BUFSIZE, 11
 fstab file, 95

G

gadm device, 82
 gadm device format, 83
 General configuration, 7
 Generation parameters, 27
 Generation software (CONFIG_GENBIN), 30
 Generation software directory paths, 30
 gether device, 82
 gether device format, 83
 getty command, 96
 gettydefs file, 96
 gfddi device format, 83
 ghippi device, 82
 ghippi device format, 83
 ghippi#.arp file, 97
 GigaRing configuration parameters (gigaring section), 39
 GigaRing device types, 82
 gigaring section, 39
 GigaRing support
 GigaRing based systems, 28
 IOS-E based systems, 29
 gr_route subsection, 40
 gr_union subsection, 40
 group file, 97
 Guest resource table entries, 50
 Guest systems, 50
 GUESTMAX parameter, 50

H

Handles, 75
 Hash entries (NHBUF_FCTR) , 9

HDD
 (See High performance parallel interface disk devices), 52
 HDDMAX parameter, 52
 HDDSLMAX parameter, 52
 Hertz, 6
 hi device, 82
 hidev device format, 84
 hidirmode parameter, 75
 hifilemode parameter, 75
 High Performance Parallel Interface, 76
 High performance parallel interface (HIPPI) disk devices, 52
 High-speed (HISP) , 41
 High-speed channel (HISP) declarations in CSL, 43
 High-speed HIPPI device, 82
 himaxdevs parameter, 76
 himaxpaths parameter, 76
 HIPPI directory mode, 75
 hippi_disk device type, 57
 HISP
 (See High-speed (HISP) channel information), 41
 HPN bit and range numbers, 52
 HSX device driver, 31
 hycf.* file, 98
 HZ, 6

I

I/O clusters, 41
 I/O error logging, 22
 I/O module 0 channels, 47
 I/O node unit bit and range numbers, 52
 I/O processor
 boot declarations, 43
 I/O processor (IOP) declarations in CSL, 42
 I/O processors, 41
 ICMS

- (See Installation and configuration menu system (ICMS)), 1
- Identifiers in CSL, 33
- IEEE and Cray floating-point, 31
- In-core inode table, 9
- In-core inodes, 9
- In-core inodes for NC1FS (file system migration parameter) , 11
- In-core quota entries, 10
- Informational messages and CSL, 36
- initif command
 - use of interfaces file, 99
- inittab file, 98
- Install tool
 - (See Installation and configuration menu system (ICMS)), 1
- Installation, 1
- Installation and configuration menu system (ICMS), 1
- Integrity code in secure.c, 18
- Interface configuration templates, 80
- interfaces file, 99
- Internal routing, 39
- Internet Protocol (IP) layer activity logging, 21
- Introduction, 1
- IOC
 - (See I/O clusters), 41
- ION
 - (See I/O node), 52
- IOP
 - (See I/O processors), 41
- iopath, 60
- IOS-E hardware topology definition, 41
- IOS-E machines, 29
- IOS-E serial numbers, 29
- ios_e section, 41
- iounit, 59
- IPC kernel parameters, 15
- IPI-2 disk type, 57
- IPI-3/HIPPI packet driver capability, 31
- IPI-3/IPI capability, 31
- IPN bit and range numbers, 52
- issue file, 99

J

- job end logging , 21
- Job start logging, 21

K

- K_OPEN_MAX, 11
- Kerberos support, 31
- Kernel generation parameters, 27
- Kernel memory parameters, 12
- Kernel parameters, 1
 - common, 8
- Kernel subsystem parameters, 27
- Kernel subsystems
 - (See config.mh configuration file), 1
- Keyword identifiers in CSL, 34
- KM_CHM_PADSZ parameter, 12
- KM_EXPAND_UNITS, 12
- KM_NO_THRASH parameter, 12
- KM_UNITS parameter, 13
- KM_WPU parameter, 13
- KM_WPU_SHIFTC parameter, 13

L

- ldcache blocks, 8
- Ldcache headers, 50
- LDCHCORE, 8, 39
- LDCHCORE parameter, 50
- ldchlist file, 99
- LDD
 - Logical disk devices , 51
- ldd logical device, 65
- LDDMAX parameter, 51
- Libraries, cross-targeted, 30
- Limits parameters, 50
- link call logging, 20
- Link violation logging, 21
- LINK_MAX , 8

Links to a file, 8
 Log records for the file system, 11
 LOGDELAY, 18
 Logging parameters for MLS, 20
 Logical device cache headers, 9
 Logical devices in CSL, 34
 Logical disk devices (LDDs), 51
 logical path statement, 84, 81
 Login account disabling, 18
 Login attempts, 17
 login attempts, 18
 Login failure logging, 22
 Low-speed channel, 82
 Low-speed channel communication devices, 76

M

Machine-specific characteristics, 1
 Mainframe cluster registers, 45
 Mainframe memory size, 46
 mainframe section, 44
 Mainframe serial number, 4
 Mainframe subtype, 5
 Mainframe type, 5
 Major release number, 30
 Managed memory buffers, 23, 75
 Mandatory access request logging, 22
 MAX_UNLINKED_BYTES parameter, 11
 MAXASYN, 8
 maxinputs parameter, 76
 MAXLOGS, 18
 maxoutputs parameter, 76
 MAXPIPE, 8
 MAXRAH, 8
 MAXSLEVEL, 18
 maxusers parameter, 76
 MAXUSRERR, 15
 MAXUSRORE parameter, 15
 MAXUSRPRE parameter, 15
 MDD
 (See Mirrored disk device), 51
 mdd mirrored device, 66

MDDSLMAX parameter, 51
 MEMORY, 4
 Memory banks, 4
 Memory buffers, 75
 Memory buffers for TCP/IP, 23
 Memory padding, 12
 memory range, 39
 Memory size, 46
 Menu system
 (See Installation and configuration menu
 system (ICMS)), 1
 Message header number, 16
 Message interval, 24
 Message queue maximum bytes, 15
 Message queue maximum number, 15
 Message segment number, 16
 Message segment size, 16
 Message size, 15
 Messages and CSL, 36
 MFSUBTYP, 5
 MFTYPE, 5
 Minor release number, 30
 MINSLEVEL, 18
 Mirrored disk device (MDD) slices, 51
 Mixed buffer, 11
 Mixed mode (Cray floating-point and IEEE), 31
 mkdir call logging, 20
 mkdir violation logging, 22
 MLS, 7
 MLS administration console, 22
 MLS kernel parameters, 17
 MLS_INTEGRITY, 18
 MLS_OBJ_RANGES, 18
 motd file, 100
 MPN bit and range numbers, 52
 MSGMAX, 15
 MSGMNB, 15
 MSGMNI, 15
 msgque table size, 15
 MSGSEG, 15
 MSGTQL, 16
 Multilevel security (MLS), 7

muxiop statement, 42

N

Name of the system, 28

NASYN, 8

NBANKS, 4

NBLK_FCTR, 8

NBUF parameter, 50

NBUF_FCTR, 8

NC1FS in-core inodes , 11

NC1INODE, 9, 11

NC1MINRAW, 11

NC_NAMLEN, 9

NC_SIZE, 9

NCALL, 9

NCLIST, 9

NCPU, 6

NCRBUF, 9

netvar.conf file, 101

Network access violation logging, 22

Network device prototypes for IOS-E based systems, 78

Network device types

IOS-E based, 82

Network devices, 81

Network File System, 32

Network File System with Kerberos authentication, 32

Network monitor, 31

Network parameters

common, 74

IOS-E, 77

menu, 74

network section, 73

Network testing tools, 32

NEXECS, 9, 11

NFILE, 9

NFLOCKS, 9

NFS

(See Network File System), 32

NFS activity logging , 20

NFS kernel parameters

(See config.h configuration file), 23

NFS kernel parameters and their CSL boot-time equivalents , 25

NFS requests, 75

NFS version 3 Protocol, 32

NFS-mounting of a remote file system in read-write mode , 18

NFS3_ASYNC_MAX, 23, 25

nfs3_async_max, 25

nfs3_async_max parameter, 75

NFS3_ASYNC_TIME, 23

nfs3_async_time, 25

nfs3_async_time parameter, 75

nfs_duptimeout, 25

NFS_DUPTIMEOUT parameter, 23

nfs_duptimeout parameter, 75

NFS_MAXDATA, 23

nfs_maxdata, 25

nfs_maxdata parameter, 75

NFS_MAXDUPREQS, 23

nfs_maxdupreqs, 25

nfs_maxdupreqs parameter, 75

nfs_num_rnodes parameter, 75

nfs_num_rnodes&, 25

NFS_PRINTINTER, 24

nfs_printinter, 25

nfs_printinter parameter, 75

NFS_REMOTE_RW_OK parameter, 18

NFS_SECURE_EXPORT_OK, 18

NFS_STATIC_CLIENTS, 24

nfs_static_clients, 25

nfs_static_clients parameter, 75

NFS_TEMP_CLIENTS, 24

nfs_temp_clients, 25

nfs_temp_clients parameter, 75

NGRT parameter, 50

NHBUF_FCTR, 9

Nice value, 11

NINODE, 9

NLDCH, 9

NLDCH parameter, 50

NLDMAP, 9
 NMNT, 9
 NMOUNT parameter, 9
 NMT, 12
 Node name of the system, 28
 Node number, 24
 non-inode security system call logging, 21
 Non-tape daemon tapes., 12
 np_spec statement, 78, 81
 NPBUF, 10
 NPBUF parameter, 50
 npdev device, 82
 npdev device format, 84
 npdirmode, 77
 npfilemode parameter, 76
 npito, 77
 NPLCHCTL, 10
 npmaxdevs, 76
 npmaxpaths parameter, 77
 npmaxppd parameter, 77
 npoto parameter, 77
 NPROC, 10
 nprthresh parameter, 77
 nprto parameter, 77
 NPTY , 10
 npwthresh parameter, 77
 NQS activity logging, 20
 NQUOTA, 10
 NSESS, 10
 NSIDEBUF, 10
 NSU_ASYN, 10
 NTEXT, 10
 Number of CPUs, 6
 NUSERS, 10

O

Object identifiers in CSL, 34
 Object ranges, 18
 Offline file retrieval mode , 8
 ONFIG_CAM_CPP_LOC, 29
 Online diagnostics location, 27

Online tape capability, 32
 Online tape parameters, 50
 Open files per process , 11
 Operand range error maximum, 15
 Operating mode information, 41
 Operating system identification, 28
 GigaRing based systems, 28
 IOS-E based systems, 29
 Operator action logging, 21
 Operator workstation, 32
 Operators in CSL, 35
 Output time-out, 77
 OVERWRITE_COUNT, 18
 OWS
 (See Operator workstation), 32
 OWS path names, 41

P

Packaging, 30
 Panic messages and CSL, 36
 Parameter file, 33
 Parameter file sections
 (See Configuration specification language
 (CSL) parameter file), 36
 Partition cache blocks, 11
 Partition cache headers, 10
 PASS_MAXSIZE, 18
 PASS_MINSIZE, 19
 passwd file, 101
 Password size maximum, 19
 Password size minimum, 19
 Passwords enabled, 19
 Path name access tracking, 22
 Path selection, 39
 PDD
 (See Physical disk devices), 51
 pdd physical device, 65
 PDDMAX parameter, 51
 PDDSLMAX parameter, 51
 Permissions, 77

Physical devices, 52
 Physical devices in CSL, 34
 Physical disk devices (PDDs), 51
 Physical I/O buffers, 50
 Physical I/O error logging, 22
 Physical I/O headers (NPBUF) , 10
 Physical memory size, 4
 Physical slices, 52
 Pipe device block allocation, 8
 pipes , 18
 PLCHCORE, 10, 39
 PRIV_SU, 19
 Privilege logging, 21
 Process error thresholds, 15
 Processes that may be active simultaneously
 (NPROC) , 10
 profile file, 102
 Program range error maximum, 15
 Programming environment parameters, 27, 32
 Prototype network devices for IOS-E based
 systems, 78
 Pseudo terminals (tty/pty pairs), 10

Q

qdd physical device, 66
 Quota entries, 10
 Quotas for files, 31

R

RAID bit and range numbers, 52
 RAM
 (See Random access memory), 39
 RAM device type, 57
 Random access memory (RAM) disk, 39
 Random access memory (RAM) disk device
 (RDD) slices, 51
 RANDOM_PASS_ON, 19
 Range numbers
 unit bit and , 52

rcoptions file, 102
 RDD
 (See Random access memory (RAM) disk
 device), 51
 RDDSLMAX parameter, 51
 Read down on pipes , 20
 Read-ahead blocks per read operation, 8
 Release number, 30
 release number (CONFIG_RLS_REVISION), 30
 Remote process control system, 32
 Remove request logging, 20
 Repeatable relocatables capability, 30
 Request cache, 75
 Request cache size, 24
 Reserved keywords in CSL, 105
 Restart and checkpoint buffers, 9
 Retired security logs, 21
 Retrieval mode for offline files, 8
 Revision identifiers in CSL, 34
 revision section, 89
 rm call logging, 20
 rm violation logging, 22
 rmdir call logging, 20
 rmdir violation logging, 22
 Rnode number, 24
 Rnode table for NFS, 75
 Root privilege, 19
 ROOTDIR, 49
 Routing, 39
 RPC
 (See Remote process control system), 32

S

SANITIZE_PATTERN, 19
 scrub pattern for disks, 19
 Scrubbing of data, 20
 sdaemon command
 use of daemons file, 94
 SDD
 (See Striped disk device), 51

- sdd striped device, 66
- SDDSLMAX parameter, 51
- Secure file system export, 18
- SECURE_MAC parameter, 19
- SECURE_OPERATOR_CONSOLE, 19
- SECURE_PIPE, 20
- SECURE_SCRUB, 20
- SECURE_SYSTEM_CONSOLE parameter, 20
- security, 22
- Security level minimum, 18
- Security levelmaximum, 18
- Security log buffer size, 20
- Security log name, 20
- Security log size, 22
- security logs location, 20
- Security logs, retired, 21
- SEMAEM, 16
- Semaphore individual value, 17
- Semaphore sets, 16
- Semaphores in the system, 16
- Semaphores per set, 17
- SEMMNI, 16
- SEMMNS, 16
- SEMMNU, 16
- SEMMSL, 16
- semop system call adjust-on-exit value , 16
- semop system call operations, 17
- SEMOPM, 17
- SEMUME, 17
- SEMVMX, 17
- Separators in CSL, 35
- Serial number, 28
- Sessions open simultaneously, 10
- setuid / setgid files , 18
- setuid system call logging, 22
- Shared memory identifiers, 14
- Shared memory kernel parameters, 14
- Shared memory parameters, 14
- Shared segment size maximum, 14
- shared segment size minimum, 14
- Shared segments , 14
- Shared-text programs that can be running simultaneously, 10
- shmem table size , 14
- SHMMAX, 14
- SHMMIN, 14
- SHMMNI, 14
- SHMSEG, 14
- shutdown shell script, 103
- Side door buffer, 10
- SIGCPULIM signal, number of CPU seconds that a process or session may use following , 11
- SLG_ACT_NFS, 20
- SLG_ACT_NQS, 20
- SLG_ALL_NAMI, 20
- SLG_ALL_RM, 20
- SLG_ALL_VALID, 20
- SLG_BUFSIZE, 20
- SLG_CF_UNICOS, 20
- SLG_DIR, 20
- SLG_DISCVconfig.h configuration file discretionary access violations (SLG_DISCV), 20
- SLG_FILE, 20
- SLG_FILEXFR, 20
- SLG_FPREFIX, 20
- SLG_JEND, 21
- SLG_JSTART, 21
- SLG_LINKV, 21
- SLG_LOG_AUDIT, 21
- SLG_LOG_CHDIR, 21
- SLG_LOG_CRL, 21
- SLG_LOG_DAC parameter, 21
- SLG_LOG_IPNET parameter, 21
- SLG_LOG_OPER, 21
- SLG_LOG_PRIV, 21
- SLG_LOG_SECSYS parameter, 21
- SLG_LOG_SHUTDOWN, 21
- SLG_MANDV, 21
- SLG_MAXSIZE parameter, 22
- SLG_MAXSIZEconfig.h configuration file , 22
- SLG_MKDIRV, 22
- SLG_NETWV, 22

SLG_PATH_TRACK, 22
 SLG_PHYSIO_ERR, 22
 SLG_REMOVEV, 22
 SLG_RMDIRV, 22
 SLG_STATE, 22
 SLG_SUID_RQ, 22
 SLG_SULOG, 22
 SLG_T_PROC, 22
 SLG_USER, 22
 SLGOFF, 21
 Slice structures , 9
 Slices in CSL, 34
 SN, 4
 sn.h configuration file, 1, 3
 Socket space , 74
 sockets, 18
 Spare chip configuration, 48
 SSD, 38, 43, 44, 48, 49
 SSD device type, 57
 SSD logical device cache headers, 9
 SSD side door buffer, 10
 SSD-T90 device type, 57
 SSD-T90 devices, 51
 SSD-T90 slice allocation, 52
 SSDT, 55
 SSDTMAX parameter, 51
 SSDTSLMAX parameter, 51
 Static client handles in CNFS
 (CNFS_STATIC_CLIENTS), 24
 Static client handles in NFS
 (NFS_STATIC_CLIENTS), 24
 Striped disk device (SDD) slices, 51
 Structures in the system, 16
 su command attempt logging, 22
 Subdirectory permissions, 77
 Subsystem parameters, 27
 Subsystems
 (See config.mh configuration file), 1
 Support software directory, 30
 System compartments, 22
 System dump parameters , 38
 system high/system low MAC, 19
 System parameters, 27

System shutdown logging, 21
 System workstation
 (See Operator workstation), 32
 SYSTEM_ADMIN_CONSOLE, 22
 SYSVCOMPS, 22

T

Table size parameters, 50
 Tape capability, 32
 Tape devices, 50
 Tape parameters, 50
 TAPE_MAX_CONF_UP parameter, 50
 TAPE_MAX_DEV parameter, 50
 TAPE_MAX_PER_DEV parameter, 50
 Target information, 41
 Target of the system to generate, 28
 TCP/IP, 7
 TCP/IP kernel parameters, 23
 TCP/IP managed memory buffers, 23, 75
 TCP/IP network system, 32
 TCP_NMBSPACE, 23
 tcp_numbspace parameter, 75
 Temporary client handles in CNFS, 24
 temporary client handles in CNFS
 (CNFS_TEMP_CLIENTS), 24
 Temporary client handles in NFS, 24
 temporary client handles in NFS
 (NFS_TEMP_CLIENTS), 24
 Temporary-file directory, 28
 Terminal I/O buffers, 9
 Time out, 77
 tmttype, 59
 Trusted process activity logging, 22
 Trusted UNICOS, 32
 tty/pty pairs, 10
 Tunable parameters, 50

U

- U_MAXDEV, 12
- U_MAXPACK, 11, 12
- umountem shell script, 103
- Undo entries per process, 17
- UNICOS installation, 1
- unicos section, 49
- UNICOS statement, 49
- UNICOS/mk operating system
 - GigaRing based systems, 28
 - IOS-E based systems , 29
- Unique files that can be open at one time, 9
- Unlinked files for checkpoint and restart , 11
- user devices , 12
- User number defined for the fair share
 - scheduler , 10
- user packets , 11, 12
- uts kernel, 31

V

- Version name, 28

W

- Words per unit of dynamic kernel memory, 13
- Write cache, 23

X

- xdd, 59
- XDDMAX parameter, 52
- xddphyscial device, 66
- XDDSLMAX parameter, 52
- xdisk, 56, 57
- XTRASEC, 11